

GEAR OIL

80W-90

GL-5

Verus Gear Oil 80W-90 GL-5 is designed for use in hypoid, bevel and spiral gear units, axles and final drives operating over a wide spectrum of severe conditions.

Verus Gear Oil 80W-90 GL-5 meets the requirements of several automotive manufacturers for passenger cars, commercial trucks and buses.

FEATURES AND BENEFITS

- Very good wear protection, even under severe load conditions
- High safety margin against foaming and corrosion
- Superior viscosity/temperature and cold flow properties
- Compatible with all seal and metal types

APPLICATIONS

- For use in hypoid, bevel and spiral gear units, axles, and final drives

SPECIFICATIONS

Meets or exceeds the requirements of:

- API GL-5
- MIL-L-2105 D



Available in: 20L | 205L | 1000L

TECHNICAL DATA

| Characteristic | Test Method | Result |
|--|-------------|----------------|
| Physical Appearance | Visual | Bright & Clear |
| Density @ 15°C cSt | ASTM D 1298 | 0.904 |
| Viscosity @ 100°C cSt | ASTM D 445 | 18.02 |
| Viscosity Index | ASTM D 2270 | 96 |
| Pour Point °C | ASTM D 97 | -21 |
| Flash Point °C | ASTM D 92 | 220 |
| Brookfield Viscosity Max Temp for Visc of 1,50,000 cP °C | ASTM D 2983 | 102,000 |