

GEAR OIL

85W-140

GL-5

Verus Gear Oil 85W-140 GL-5 is designed for use in hypoid, bevel and spiral gear units, axles and final drives operating over a wide spectrum of severe conditions.

Verus Gear Oil 85W-140 GL-5 meets the requirements of several automotive manufacturers for passenger cars, commercial trucks and buses.

FEATURES AND BENEFITS

- Very good wear protection, even under severe load conditions
- High safety margin against foaming and corrosion
- Superior viscosity/temperature and cold flow properties
- Compatible with all seal and metal types

APPLICATIONS

- For use in hypoid, bevel and spiral gear units, axles, and final drives

SPECIFICATIONS

Meets or exceeds the requirements of:

- API GL-5
- MIL-L-2105 D
- Also recommended by numerous vehicle manufacturers such as Iveco, Man, Scania, and Volvo for heavy vehicles rear axles and final drive units.



Available in: 20L | 205L | 1000L

TECHNICAL DATA

Characteristic	Test Method	Result
Physical Appearance	Visual	Bright & Clear
Density @ 15°C cSt	ASTM D 1298	0.91
Viscosity @ 100°C cSt	ASTM D 445	26.02
Viscosity Index	ASTM D 2270	98
Pour Point °C	ASTM D 97	-18
Flash Point °C	ASTM D 92	232