

# TRANSMISSION DRIVE-TRAIN OIL

## SAE 10W TO-4

TDTO – A transmission drive-train oil for final drives, power-shift transmissions, torque converters, hydraulic systems requiring an ISO 32 fluid and off-highway equipment



Available in: 20L | 205L | 1000L

Verus TDTO SAE 10W is an extra high-performance transmission and drive-train lubricant formulated to meet rigorous specifications required by Caterpillar TO-4. Verus TDTO SAE 10 is designed to optimise the performance of power shift transmissions, gear boxes and final drives. In hydraulic applications, it provides maximum protection even in high-pressure systems.

The technology in this formulation combines selected base oils and an advanced additive package to deliver the precise performance parameters needed to maximize the productivity of construction, quarrying and mining equipment operating in severe conditions. Verus TDTO SAE 10W offers a clear performance advantage over the use of mixed fleet engine oils and previously used lubricants meeting Caterpillar TO-2.



p: 1800 243 628 | [aus-sales@chematek.com](mailto:aus-sales@chematek.com) | [w: chematek.com](http://w:chematek.com)



# TRANSMISSION DRIVE-TRAIN OIL SAE 10W

## FEATURES AND BENEFITS

- Provides balanced static dynamic friction coefficients for optimized clutch-free retention and slippage control
- Compatible with the latest clutch materials ensuring longer clutch life and higher performance
- Increased levels of anti-wear and load carrying capability for greater productivity and reduced down-time
- Excellent foam control protection for reliable performance in wet brakes and increased control of brake chatter
- Excellent thermal and oxidation stability for protection against high-pressure pump wear
- Very good low temperature pumpability for reduced start-up to production times

## APPLICATIONS

Some typical applications include:

- Heavy duty transmissions, gear boxes, final drives and hydraulic systems used in on and off-highway applications
- Off-highway industries including mining, construction, quarrying and agriculture

## SPECIFICATIONS

Meets or exceeds the requirements of:

- Caterpillar TO-4
- Allison C-4
- ZF-TE-ML-03C



## TECHNICAL DATA

Characteristic	Test Method	Result
Physical Appearance	Visual	Bright & Clear
Viscosity @ 40° cSt	ASTM D 445	42
Viscosity @ 100° cSt	ASTM D 445	6.3
Viscosity Index	ASTM D 2270	96