

DESCRIPTION

Verus Blue LC2 Grease is formulated with a lithium complex thickener combined with a blend of high viscosity index mineral oils, selected extreme pressure additives, rust and oxidation inhibitors plus a tackiness agent. Verus Blue LC2 Grease is recommended for use where bearings are subjected to high operating temperatures.

FEATURES AND BENEFIT

- Excellent anti-wear and EP properties
- Superior adhesion and cohesion properties
- Resistance to water wash-out
- Good pumpability in low temperatures
- Resistant to rust and corrosion

APPLICATIONS

- Automotive, industrial, mining and earthmoving wheel bearings
- Disc brakes, chassis, high speed ball and roller bearings
- Boat trailer wheel bearings, water pumps, winches

SPECIFICATIONS

Meets or exceeds the requirements of:

- ISO 6743-9: L-XBEHB2
- DIN 51502: KP2P-20

TECHNICAL DATA

CHARACTERISTIC	TEST METHOD	RESULT
Consistency (NLGI Grade)	NLGI	2
Thickener Type	-	Lithium Complex
Colour/Appearance	-	Blue/Tacky
Worked Penetration (60 strokes)	ASTM D217	265-295
4-Ball Weld Load (kgf)	ASTM D2596	315
Dropping Point (°C)	ASTM D2265	260
Base Oil Viscosity @ 40 °C (cSt)	ASTM D445	200
Operating Temperature Range (°C)	-	-20 to 160
Water Washout	ASTM D1264	<5%

The information contained herein is subject to change without notification. Typical properties may vary slightly.