

DESCRIPTION

Verus Red Ultra Tack Heavy Duty (HD) Grease is formulated using a lithium complex thickener combined with high quality paraffinic and polybutene base stocks, extreme pressure (EP) additives, effective rust, oxidation and corrosion inhibitors, plus a super tackiness agent.

Verus Red Ultra Tack HD Grease is recommended for use in automotive, marine, agricultural and industrial applications that require a grease with a very high base oil viscosity and weld load.

FEATURES AND BENEFIT

- Excellent anti-wear and EP properties
- Prevention of scuffing and wear
- Resistance to water wash-out and squeeze-out even under high load conditions
- Superior adhesion and cohesion properties
- High shear stability ensuring longer service intervals
- Protection against rust and corrosion in harsh and extreme environments

APPLICATIONS

- Slow speed (low speed factor) heavily loaded anti-friction and plain bearings
- Heavy load, high pressure industrial applications
- Gears and couplings

*** Not recommended for use in auto lubricators or high-speed bearings ***

SPECIFICATIONS

Meets or exceeds the requirements of:

- ISO 6743-9: L-XBEHB2
- DIN 51502: KP2P-20

TECHNICAL DATA

CHARACTERISTIC	TEST METHOD	RESULT
Consistency (NLGI Grade)	NLGI	2
Thickener Type	-	Lithium Complex
Colour/Appearance	-	Red/Tacky
Worked Penetration (60 strokes)	ASTM D217	265-295
4-Ball Weld Load (kgf)	ASTM D2596	315
Dropping Point (°C)	ASTM D2265	250
Base Oil Viscosity @ 40 °C (cSt)	ASTM D445	1600
Operating Temperature Range (°C)	-	-20 to 160

The information contained herein is subject to change without notification. Typical properties may vary slightly.