

DESCRIPTION

Verus Gear Oil 85W-140 GL-5 is designed for use in hypoid, bevel and spiral gear units, axles and final drives operating over a wide spectrum of severe conditions.

Verus Gear Oil 85W-140 GL-5 meets the requirements of several automotive manufacturers for passenger cars, commercial trucks and buses.

FEATURES AND BENEFITS

- Very good wear protection, even under severe load conditions
- High safety margin against foaming and corrosion
- Superior viscosity/temperature and cold flow properties
- Compatible with all seal and metal types

APPLICATIONS

For use in hypoid, bevel and spiral gear units, axles, and final drives.

SPECIFICATIONS

Meets or exceeds the requirements of:

- API GL-5
- MIL-L-2105 D

Also recommended by numerous vehicle manufacturers such as Iveco, Man, Scania, and Volvo for heavy vehicles rear axles and final drive units.

TECHNICAL DATA

CHARACTERISTIC	TEST METHOD	RESULT
Physical Appearance	Visual	Bright and Clear
Density @ 15°C gm/cm ³	ASTM D 1298	0.91
Viscosity @ 100°C cSt	ASTM D 445	26.02
Viscosity Index	ASTM D 2270	98
Pour Point °C	ASTM D 97	-18
Flash Point °C	ASTM D 92	232

The information contained herein is subject to change without notification. Typical properties may vary slightly.