

DESCRIPTION

Verus Gear Oil S 75W-90 GL-4/5 is a premium full synthetic lubricant designed for manual transmissions and differentials that require API GL-4 or GL-5 performance levels. It is specifically formulated to provide optimal lubrication for both gearboxes and differentials in modern vehicles. Additionally, it is suitable for use in gearboxes of outboard engines and sterndrive systems.

Verus Gear Oil S 75W-90 GL-4/5 is strongly recommended for lubricating axles, differentials, final drives, non-synchromesh manual transmissions, transfer cases, and other gear systems that demand extended drain performance and operate under extreme pressure and shock loading conditions.

FEATURES AND BENEFITS

- Optimised for high ambient and elevated oil temperatures
- Delivers exceptional protection in severe service applications
- Guarantees exceptional thermo-oxidative stability
- Provides excellent protection against corrosion
- Ensures full seal compatibility
- Meets the most demanding OEM specifications for long-drain operations

APPLICATIONS

Verus Gear Oil S 75W-90 GL-4/5 is ideal for heavy-duty drivetrains used in both on-road and off-road applications, including trucking, construction, mining, and agriculture.

Verus Gear Oil S 75W-90 GL-4/5 is suitable for use in vehicles from Volvo, DAF, Iveco, Mack, Mercedes-Benz, Scania, Renault, and MAN, as well as those equipped with Arvin Meritor and ZF components.

SPECIFICATIONS

Meets or exceeds the requirements of:

- API GL-4/GL-5
- API MT-1
- MB 235.8
- MAN 342 type S1
- MAN 342 type Z2
- Volvo 97312
- SAE J 2360 (MIL-PRF-2015E)
- MACK GO-J
- Scania STO 2:0 A FS
- Arvin Meritor 076-N
- ZF TE-ML 02B, 05A, 12L, 12N, 16F, 17B, 19C, 21A

TECHNICAL DATA

CHARACTERISTIC	TEST METHOD	RESULT
Physical Appearance	Visual	Bright and Clear
Density @ 15°C gm/cm ³	ASTM D 1298	0.865
Viscosity @ 40°C cSt	ASTM D 445	118
Viscosity @ 100°C cSt	ASTM D 445	16.98
Viscosity Index	ASTM D 2270	157
Pour Point °C	ASTM D 97	-39
Flash Point °C	ASTM D 92	226

The information contained herein is subject to change without notification. Typical properties may vary slightly.