

Product Data Sheet: VM5907**Issue Date: 251121****Bellator by Verus**

Your vehicle deserves champion-level protection. Bellator – meaning ‘warrior’ – fights friction, heat, and deposits for smooth, efficient performance. Powered by Italian engineering and proven worldwide, Bellator lubricants keep your engine and driveline ready for battle.

Created by Italian lubricant experts, Verus blends decades of lubrication science with performance trusted by equipment manufacturers worldwide. We control every step – from formulation to delivery – ensuring speed, precision, and reliability.

As your lubrication partner, we provide technical insight, rapid solutions, and flexible options, from tailored blends to custom packaging.

Product Description

Top-performance synthetic engine oil delivering exceptional efficiency, ultra-fast cold start protection and strong LSPI defence for advanced petrol and diesel engines. Its full synthetic base keeps engines clean under extreme heat, meeting ACEA C5/C6 and API SP for modern high-efficiency, turbocharged and hybrid applications.

Features & Benefits

- Ultra-high performance synthetic base oils
- Excellent fuel economy
- Arctic cold start protection
- Cleans sludge & varnish at high temps
- Exceeds global OEM requirements

Applications

Suitable for modern petrol and diesel engines requiring API SP/SN+ and ACEA C5/C6.

Specifications

- API SP/SN+
- ACEA C5/C6
- ILSAC GF-6A
- Chrysler MS 6395
- FIAT 9.55535-CR1 / GSX
- Ford WSS-M2C947-A / B1 / WSS-M2C962-A1
- MB 229.71



Top Synthetic

Verus Bellator X 0W20 C5/C6



Technical Data

Characteristics	Test Method	Result
Physical Appearance	Visual	Bright and Clear
Density @ 15°C	ASTM D4052	0.837
Viscosity @ 40°C	ASTM D445	43.8
Viscosity @ 100°C	ASTM D445	8.5
Viscosity Index	ASTM D2270	176
Total Base Number	ASTM D2896	7.5
Pour Point	ASTM D97	-48
Flash Point	ASTM D92	226

Chematek S.p.A. operates under the European Engine Lubricant Quality Management System (EELQMS) and adheres to the ATIEL Code of Practice for developing and marketing lubricants making ACEA performance claims.

Disclaimer: The Verus logo is a trademark of Chematek SpA. Data is provided as a guide only; no warranties are given regarding accuracy or suitability. Users must ensure product suitability for their intended application, refer to the latest version of this document and the Safety Data Sheet, and always follow the equipment manufacturer's guidelines and manuals. Chematek SpA accepts no liability for misuse or failure to follow recommendations.

