

Product Data Sheet: VM5913**Issue Date: 251121****Bellator by Verus**

Your vehicle deserves champion-level protection. Bellator – meaning ‘warrior’ – fights friction, heat, and deposits for smooth, efficient performance. Powered by Italian engineering and proven worldwide, Bellator lubricants keep your engine and driveline ready for battle.

Created by Italian lubricant experts, Verus blends decades of lubrication science with performance trusted by equipment manufacturers worldwide. We control every step – from formulation to delivery – ensuring speed, precision, and reliability.

As your lubrication partner, we provide technical insight, rapid solutions, and flexible options, from tailored blends to custom packaging.

Product Description

A premium full synthetic oil engineered for high-output petrol and diesel engines requiring maximum protection. Provides rapid cold-start lubrication, exceptional high-temperature cleanliness and strong wear control. Formulated to meet the performance needs of engines requiring BMW LL-01, MB 229.3/229.5, Porsche A40 and VW 502/505 levels.

Features & Benefits

- Proprietary ultra-high performance synthetic base stocks
- Wide viscosity range for protection and fuel savings
- Excellent cold-start performance
- Cleans deposits, sludge and varnish
- Exceeds global industry and OEM standards

Applications

Meets/exceeds latest API & ACEA petrol engine oil requirements. Suitable for high-performance turbo-charged, supercharged petrol & diesel engines in passenger cars, SUVs, vans and trucks.

Specifications

- API SP, SN+, SN/CF
- ACEA A3/B3, A3/B4
- BMW LL-01
- VW 502 00, 505 00
- GM Dexos 1 Gen 2
- Opel OV0401547 G30
- MB 229.3, 229.5
- FORD WSS-M2C937-A
- Porsche A40



Top Synthetic

Verus Bellator X 0W40 A3/B4



Technical Data

Characteristics	Test Method	Result
Physical Appearance	Visual	Bright and Clear
Density @ 15°C, gm/cm ³	ASTM D4052	0.838
Viscosity @ 40°C cSt	ASTM D445	78.3
Viscosity @ 100°C cSt	ASTM D445	13.8
Viscosity Index	ASTM D2270	182
Total Base Number	ASTM D2896	10
HTHS at 150°C, cP	ASTM D6616	≥3.5
Pour Point °C	ASTM D97	-48
Flash Point °C	ASTM D92	228

Chematek S.p.A. operates under the European Engine Lubricant Quality Management System (EELQMS) and adheres to the ATIEL Code of Practice for developing and marketing lubricants making ACEA performance claims.

Disclaimer: The Verus logo is a trademark of Chematek SpA. Data is provided as a guide only; no warranties are given regarding accuracy or suitability. Users must ensure product suitability for their intended application, refer to the latest version of this document and the Safety Data Sheet, and always follow the equipment manufacturer's guidelines and manuals. Chematek SpA accepts no liability for misuse or failure to follow recommendations.

