

Product Data Sheet: VM5005**Issue Date: 251121****Bellator by Verus**

Your vehicle deserves champion-level protection. Bellator – meaning ‘warrior’ – fights friction, heat, and deposits for smooth, efficient performance. Powered by Italian engineering and proven worldwide, Bellator lubricants keep your engine and driveline ready for battle.

Created by Italian lubricant experts, Verus blends decades of lubrication science with performance trusted by equipment manufacturers worldwide. We control every step – from formulation to delivery – ensuring speed, precision, and reliability.

As your lubrication partner, we provide technical insight, rapid solutions, and flexible options, from tailored blends to custom packaging.

Product Description

Mid-SAPS 5W30 synthetic technology oil that protects modern engines and exhaust after-treatment hardware. Excellent sludge control, cold-start flow and oxidation stability support cleaner operation and longer drains in passenger cars and light-duty diesels requiring API SP, ACEA C2/C3, Dexos 2 or MB 229.51.

Features & Benefits

- Cleans sludge
- Excellent low temperature capability
- Improves fuel economy
- Great thermal & oxidation stability
- Longer drain intervals

Applications

Designed for modern passenger and light-duty vehicles with exhaust after-treatment.

Specifications

- API SP
- ILSAC GF-6A
- ACEA C2/C3
- GM Dexos 2
- MB 229.51
- FIAT 9.55535-G2/S2
- VW 502 00 / 505 00
- Ford WSS-M2C946-A/B1/961-A
- PSA B71 2290



Technical Data

Characteristics	Test Method	Result
Physical Appearance	Visual	Bright and Clear
Density @ 15°C	ASTM D4052	0.859
Viscosity @ 40°C	ASTM D445	57
Viscosity @ 100°C	ASTM D445	10.2
Viscosity Index	ASTM D2270	169
Pour Point	ASTM D97	-28
Flash Point	ASTM D92	228

Chematek S.p.A. operates under the European Engine Lubricant Quality Management System (EELQMS) and adheres to the ATIEL Code of Practice for developing and marketing lubricants making ACEA performance claims.

