

Verus Bellator X 5W30 C3 Long Drain

Product Data Sheet: VM5906**Issue Date: 251121**

Bellator by Verus

Your vehicle deserves champion-level protection. Bellator – meaning ‘warrior’ – fights friction, heat, and deposits for smooth, efficient performance. Powered by Italian engineering and proven worldwide, Bellator lubricants keep your engine and driveline ready for battle.

Created by Italian lubricant experts, Verus blends decades of lubrication science with performance trusted by equipment manufacturers worldwide. We control every step – from formulation to delivery – ensuring speed, precision, and reliability.

As your lubrication partner, we provide technical insight, rapid solutions, and flexible options, from tailored blends to custom packaging.

Product Description

Long-drain 5W30 synthetic for extreme performance and extended service intervals. High-stability base stocks and strong detergency protect turbocharged and supercharged engines, maintaining cleanliness and viscosity under severe duty. Meets major OEM C3 long-life specifications including VW 504/507, BMW LL-04, Dexos 2, Renault and PSA specifications.

Features & Benefits

- Ultra-high performance base stocks
- Fuel saving benefits
- Arctic cold start capability
- Cleans sludge & high-temp deposits
- Meets major builder long-life standards

Applications

Recommended for high-performance turbo/supercharged engines. Suitable for long-drain cycles.

Specifications

- API SP/SN+/SJ/CF
- ACEA C3
- ILSAC GF-6A
- GM Dexos 2
- MB 229.31/229.51/229.52
- BMW LL-04
- Porsche C30
- Renault RN0710 / RN17
- FIAT 9.55535-S3
- VW 504 00 / 507 00
- Ford WSS-M2C917-A
- PSA B71 2290 / 2297
- Opel OV0401547-D30

Disclaimer: The Verus logo is a trademark of Chematek SpA. Data is provided as a guide only; no warranties are given regarding accuracy or suitability. Users must ensure product suitability for their intended application, refer to the latest version of this document and the Safety Data Sheet, and always follow the equipment manufacturer's guidelines and manuals. Chematek SpA accepts no liability for misuse or failure to follow recommendations.



Top Synthetic

Verus Bellator X 5W30 C3 Long Drain



Technical Data

Characteristics	Test Method	Result
Physical Appearance	Visual	Bright and Clear
Density @ 15°C	ASTM D4052	0.859
Viscosity @ 40°C	ASTM D445	62.5
Viscosity @ 100°C	ASTM D445	11.0
Viscosity Index	ASTM D2270	172
Total Base Number	ASTM D2896	7.62
Pour Point	ASTM D97	-45
Flash Point	ASTM D92	228

Chematek S.p.A. operates under the European Engine Lubricant Quality Management System (EELQMS) and adheres to the ATIEL Code of Practice for developing and marketing lubricants making ACEA performance claims.

Disclaimer: The Verus logo is a trademark of Chematek SpA. Data is provided as a guide only; no warranties are given regarding accuracy or suitability. Users must ensure product suitability for their intended application, refer to the latest version of this document and the Safety Data Sheet, and always follow the equipment manufacturer's guidelines and manuals. Chematek SpA accepts no liability for misuse or failure to follow recommendations.

