## 85W140 GL-5



Product Data Sheet: VM2003 Issue Date: 251121

### **Rudis by Verus**

Transmissions drive heavy machinery, and Rudis keeps them working with dependable strength. Inspired by the Rudis - the wooden sword symbolising a gladiator's freedom - these oils are built to handle extreme loads and heat. Rudis keeps your components protected, giving your equipment the freedom to perform without breakdowns or inefficiency.

Created by Italian lubricant experts, Verus blends decades of lubrication science with performance trusted by equipment manufacturers worldwide.

We control every step - from formulation to delivery - ensuring speed, precision, and reliability.

As your lubrication partner, we provide technical insight, rapid solutions, and flexible options, from tailored blends to custom packaging.

#### **Product Description**

High-viscosity 85W140 GL-5 gear oil for hypoid and final-drive units operating under extreme load and temperature. Provides excellent wear control, cold-flow performance for its grade and strong resistance to foaming and corrosion. Recommended for severe-duty axles in passenger cars, trucks and buses, including Iveco, MAN, Scania and Volvo applications.

#### **Features & Benefits**

- Very good wear protection under severe load
- High foaming and corrosion resistance
- Superior viscosity/temperature and cold flow performance
- · Compatible with all seal and metal types

#### **Applications**

Suitable for hypoid, bevel, spiral gears, axles and final drives. Recommended by Iveco, MAN, Scania and Volvo.

## **Specifications**

- API GL-5
- MIL-L-2105 D





# 85W140 GL-5



## **Technical Data**

Characteristics	Test Method	Result
Physical Appearance	Visual	Bright and Clear
Density @ 15°C	ASTM D1298	0.91
Viscosity @ 100°C	STM D445	26.02
Viscosity Index	ASTM D2270	98
Pour Point	ASTM D97	-18
Flash Point	ASTM D92	232

Chematek S.p.A. operates under the European Engine Lubricant Quality Management System (EELQMS) and adheres to the ATIEL Code of Practice for developing and marketing lubricants making ACEA performance claims.



