

Product Data Sheet: VM2009**Issue Date: 251121****Rudis by Verus**

Transmissions drive heavy machinery, and Rudis keeps them working with dependable strength. Inspired by the Rudis – the wooden sword symbolising a gladiator's freedom – these oils are built to handle extreme loads and heat. Rudis keeps your components protected, giving your equipment the freedom to perform without breakdowns or inefficiency.

Created by Italian lubricant experts, Verus blends decades of lubrication science with performance trusted by equipment manufacturers worldwide.

We control every step – from formulation to delivery – ensuring speed, precision, and reliability.

As your lubrication partner, we provide technical insight, rapid solutions, and flexible options, from tailored blends to custom packaging.

Product Description

Heavy-duty 85W140 GL-5 limited-slip gear lubricant built for severe shock loads and high temperatures. Strong film strength, foam control and corrosion protection safeguard differentials, axles and final drives in demanding on- and off-highway service where GL-5 and MT-1 performance is required.

Features & Benefits

- Enhanced limited-slip performance
- Reduced wear & maintenance costs
- Rust, staining & corrosion protection
- Strong film strength under load
- Foam resistance
- Seal & metal compatibility

Applications

Ideal for heavy-duty differentials, axles, and final drives.

Specifications

- API GL-5
- API MT-1
- MIL-PRD-2105D
- MIL-PRF-2105E



Mineral

Verus Rudis

LS 85W140 GL-5



Technical Data

Characteristics	Test Method	Result
Physical Appearance	Visual	Bright and Clear
Density @ 15°C	ASTM D1298	0.904
Viscosity @ 100°C	ASTM D445	18.02
Viscosity Index	ASTM D2270	96
Pour Point	ASTM D97	-21
Flash Point	ASTM D92	220

Chematek S.p.A. operates under the European Engine Lubricant Quality Management System (EELQMS) and adheres to the ATIEL Code of Practice for developing and marketing lubricants making ACEA performance claims.

Disclaimer: The Verus logo is a trademark of Chematek SpA. Data is provided as a guide only; no warranties are given regarding accuracy or suitability. Users must ensure product suitability for their intended application, refer to the latest version of this document and the Safety Data Sheet, and always follow the equipment manufacturer's guidelines and manuals. Chematek SpA accepts no liability for misuse or failure to follow recommendations.

